



# BL-88A

## Slit Lamp Microscope



# BL-88A · Slit Lamp Microscope

Innovation design, filter disk can rotate 360°, 4 more option filters can be Select.

Five-step drum magnification for eyepiece. Sclera vein could be observed under the 40x magnification

All the optical lenses are moistureproof, mildewproof and anti-reflected treated

Large spot diameter, slit length reach to 14mm, more comprehensive view of the eye condition

Multi-coated optical glass technology, imaging is clear and bright, the view field is wide.

Osram light bulbs, small heat, high-brightness, spot uniformity

Handrail design, user-friendly and the convenience of patients

Oversized joystick space, move base does not touch the hand

All the joints can be connected by accessories with international standards

Microscope	Microscope Type	Galilean stereoscopic microscope
	Magnification Selection	5 steps by drum rotation
	Eyepiece	12.5x
	Magnification Ratio (Field of View)	6x(33mm), 10x(22.5mm), 16x(14mm), 25x(8.8mm), 40x(5.5mm)
	Pupillary Adjustment	50mm ~ 82mm
	Diopter Adjustment	±7D
Base	Side Shift	110mm
	Depth Shift	90mm
	Height Shift	30mm
Chin rest	Height Shift	80mm
	Fixation Target	Red LED
Illumination system	Slit Width	0 ~ 14mm Continuous(at 14mm, slit becomes a circle)
	Slit Height	1 ~ 14mm Continuous
	Slit Angle	0° ~ 180° adjustable
	Slit Inclination	5°, 10°, 15°, 20°
	Diameter of Light Spot	φ14mm, φ10mm, φ5mm, φ3mm, φ2mm, φ1mm, φ0.2mm and 1~14mm continuous
	Filter	Heat Absorption, Grey, Red-Free, Cobalt, Blue, Green, Yellow, Red, Anti-UV
	Illumination Bulb	12v 50w halogen lamp
Power	Input Voltage	110V/220V AC
	Frequency	50/60Hz
	Power Consumption	68VA
Weight And Size	Gross Weight	18kg
	Dimension	690mm (L) × 440mm (W) × 420mm (H)

Shanghai Bolan Optical-Electric Co.,Ltd